




Carbide Electro Deposited Diamond End Mill

초경 전착 다이아몬드 엔드밀



- 지르코니아(ZrO₂), E-MAX, 얼티메이트(Ultimate) 등 비철 비금속 가공 엔드밀
- 완전 소결된 지르코니아, 세라믹, 글라스 등의 가공에 적합합니다.
- 다이아몬드 입자를 니켈 도금하여 내마모 성능이 탁월합니다.
- 초경 모재를 사용하여 공구 휨이 적어 정밀가공에 적합합니다.
- Endmills for Zirconia, E-MAX, Ultimate, Non-ferrous and non-metallic materials.
- Milling process is suitable for completely sintered zirconia, ceramic and glass.
- Wear resistance is excellent by applying diamond particle with nickel plating.
- Precision processing is available with less bending on the tool with carbide material.

단위 : mm


Order Number	날경 Diameter R × D	날장 Length of cut L1	전장 Overall Length L	생크소경 Shank Dia d1	생크 Shank Dia d
EDD 006 060 340	0.3R X 0.6	6	40	1.6	3
EDD 006 060 350	0.3R X 0.6	6	50	1.6	3
EDD 006 060 440	0.3R X 0.6	6	40	2	4
EDD 006 060 450	0.3R X 0.6	6	50	2	4
EDD 006 060 640	0.3R X 0.6	6	40	4.2	6
EDD 006 060 650	0.3R X 0.6	6	50	4.2	6
EDD 010 100 340	0.5R X 1	10	40	1.6	3
EDD 010 100 350	0.5R X 1	10	50	1.6	3
EDD 010 100 440	0.5R X 1	10	40	2	4
EDD 010 100 450	0.5R X 1	10	50	2	4
EDD 010 100 640	0.5R X 1	10	40	4.2	6
EDD 010 100 650	0.5R X 1	10	50	4.2	6
EDD 015 080 450	0.75R X 1.5	8	50	2	4
NEW EDD 015 120 450	0.75R X 1.5	12	50	2	4

Order Number	날경 Diameter R × D	날장 Length of cut L1	전장 Overall Length L	생크소경 Shank Dia d1	생크 Shank Dia d
NEW EDD 015 120 650	0.75R X 1.5	12	50	4.2	6
NEW EDD 015 150 650	0.75R X 1.5	15	50	4.2	6
EDD 020 120 340	1R X 2	12	40	1.6	3
EDD 020 120 350	1R X 2	12	50	1.6	3
EDD 020 120 440	1R X 2	12	40	2	4
EDD 020 120 450	1R X 2	12	50	2	4
EDD 020 120 640	1R X 2	12	40	4.2	6
EDD 020 120 650	1R X 2	12	50	4.2	6
EDD 025 150 340	1.25R X 2.5	15	40	1.6	3
EDD 025 150 350	1.25R X 2.5	15	50	1.6	3
EDD 025 150 440	1.25R X 2.5	15	40	2	4
EDD 025 150 450	1.25R X 2.5	15	50	2	4
EDD 025 150 640	1.25R X 2.5	15	40	4.2	6
EDD 025 150 650	1.25R X 2.5	15	50	4.2	6



Steel Electro Deposited Diamond End Mill

스틸 전착 다이아몬드 엔드밀



- 지르코니아(ZrO₂), E-MAX, 얼티메이트(Ultimate) 등 비철 비금속 가공 엔드밀
- 완전 소결된 지르코니아, 세라믹, 글라스 등의 가공에 적합합니다.
- 다이아몬드 입자를 니켈 도금하여 내마모 성능이 탁월합니다.
- 다이아몬드 입자와 모재의 밀착력이 좋아, 피삭재 가공력이 뛰어납니다.
- Endmills for Zirconia, E-MAX, Ultimate, Non-ferrous and non-metallic materials.
- Milling process is suitable for completely sintered zirconia, ceramic and glass.
- Wear resistance is excellent by applying diamond particle with nickel plating.
- High adhesion of diamond particles and carbide material, milling Process is excellent on a workpiece.

단위 : mm

Order Number	날경 Diameter R × D	날장 Length of cut L1	전장 Overall Length L	생크소경 Shank Dia d1	생크 Shank Dia d
EDDH 006 060 340	0.3R X 0.6	6	40	1.6	3
EDDH 006 060 350	0.3R X 0.6	6	50	1.6	3
EDDH 006 060 440	0.3R X 0.6	6	40	2	4
EDDH 006 060 450	0.3R X 0.6	6	50	2	4
EDDH 006 060 640	0.3R X 0.6	6	40	4.2	6
EDDH 006 060 650	0.3R X 0.6	6	50	4.2	6
EDDH 010 100 340	0.5R X 1	10	40	1.6	3
EDDH 010 100 350	0.5R X 1	10	50	1.6	3
EDDH 010 100 440	0.5R X 1	10	40	2	4
EDDH 010 100 450	0.5R X 1	10	50	2	4
EDDH 010 100 640	0.5R X 1	10	40	4.2	6
EDDH 010 100 650	0.5R X 1	10	50	4.2	6
EDDH 015 080 450	0.75R X 1.5	8	50	2	4
EDDH 015 120 450	0.75R X 1.5	12	50	2	4

Order Number	날경 Diameter R × D	날장 Length of cut L1	전장 Overall Length L	생크소경 Shank Dia d1	생크 Shank Dia d
EDDH 015 120 650	0.75R X 1.5	12	50	4.2	6
EDDH 015 150 650	0.75R X 1.5	15	50	4.2	6
EDDH 020 120 340	1R X 2	12	40	1.6	3
EDDH 020 120 350	1R X 2	12	50	1.6	3
EDDH 020 120 440	1R X 2	12	40	2	4
EDDH 020 120 450	1R X 2	12	50	2	4
EDDH 020 120 640	1R X 2	12	40	4.2	6
EDDH 020 120 650	1R X 2	12	50	4.2	6
EDDH 025 150 340	1.25R X 2.5	15	40	1.6	3
EDDH 025 150 350	1.25R X 2.5	15	50	1.6	3
EDDH 025 150 440	1.25R X 2.5	15	40	2	4
EDDH 025 150 450	1.25R X 2.5	15	50	2	4
EDDH 025 150 640	1.25R X 2.5	15	40	4.2	6
EDDH 025 150 650	1.25R X 2.5	15	50	4.2	6

